

Photoelectric Beams

Honeywell's IntelliBeam™ sensors combine all the great features of high-end photobeams in a cost-effective dual detector, offering the ultimate protection at an incredible value. Available in single and dual models, there's an IntelliBeam to suit any application.



IB100D

IB200D

IB250S

FEATURES

- Single and dual beam models with range up to 250'
- Suitable for outdoor or indoor installations
- Easy alignment features reduce installation time
- Adjustable beam blocking time
- Includes pole mount kit

PRODUCT FEATURES		
	IB-200D	IB-100D
RANGE OUTDOOR	100 ft. (30m)	200 ft. (60m)
RANGE INDOOR	300 ft. (90m)	600 ft. (180m)
BEAM TYPE	Two Pulsed Beams	Two Pulsed Beams
ADJUSTABLE BEAM BLOCKING TIME	4	4
POLE MOUNT KIT INCLUDED	4	4
VERTICAL OPTICAL ADJUSTMENT	20°	20°
HORIZONTAL OPTICAL ADJUSTMENT	180°	180°
OPTICAL VIEW FINDER	Detachable	Detachable
POWER INPUT	10.5 to 26VDC	10.5 to 26VDC
CURRENT	40mA	55mA
ALARM OUTPUT	Form C	Form C
TAMPER OUTPUT	Form A	Form A
MOUNTING	Wall or Pole	Wall or Pole
OPERATING TEMPERATURE	-13°F to 131°F (-25°C to 55°C)	-13°F to 131°F (-25°C)

ORDERING

IB-100D	Dual Pulse Photobeam 100' (30m) range max. outdoor and 300' (90m) max. indoor
IB-200D	Dual Pulse Photobeam 200' (60m) range max. outdoor and 600' (180m) max. indoor

For more information:

www.honeywell.com/security

Honeywell Commercial Security

715 Peachtree Street NE
Atlanta, GA 30308
1.800.323.4576
www.honeywell.com

L/INTBEAMD/D 104/19
© 2019 Honeywell International Inc.